

FLOWERTROLLEY

Professional Flowertrolley / Agri rolley with 2 platforms

Flower cart large with tilting side rails and puncture-proof tires.

Creative aspects:

- With 2 removable side rails, height 218 mm.
- Platform of 12mm thick Plywood.
- Oval tube base, lighter and stronger.
- Puncture proof tyres. (foamed polyurethane)

Performance:

- Natural rubber handles with knuckle protection.
- · Ergonomic design.
- Handle height according to European standards.
- Finished with durable gray powder coating (no solvents, less harmful to the environment).

Wheels:

- Ø400 and Ø260 mm wheels, puncture-free with pleasant driving characteristics.
- Ø400 wheel with steel rim and double closed ball bearings.
- Ø260 wheel with plastic rim and double closed ball bearings.
- Gray tires, PU foamed Polyurethane, non-marking

• With 2 removable side rails, height 218mm.

• Net loading space platform: 1400x600 mm.

Application for the following sectors:

· Platform of 12mm thick Plywood.

Height bottom platform: 475mm.
Height top platform: 1045mm.
Handle height: 665 mm.
Load capacity 100 Kg.

Nurseries,

Garden centers.



12337 Ergo handgrip with knuckle protection



10189, M-808-CT AS Ø25MM KL



11189 M-800-CT

Cap. (kg)	Dimensions LxWxH (mm)	Dimensions platform LxWxH (mm)	Platform height - bottom - top (mm)	side rail height (mm)	Weight (kg)	Wheels Ø (mm)	Tires	Color	Plateau	Handgrip LxW (mm)	Article	Article Nr.
100	2070x661x1388	1400x600x12	- 475 - 1045	218	56,1	260 / 400	Puncture proof	Gray	Plywood 12mm	38x20	M-BLOEMENKAR GR.+ZH-2PL	19091
200	400x100				3,4	400	Puncture proof				M-800-CT	11189
200					1,6	260	Puncture proof				M-808-CT AS Ø25MM KL	10189
	130x58x90				0,18					38x20	M-970-Z RUB	12337



